

# Embedding Tearline Content Into Your Website

## 1.) Getting started

The first step towards integrating Tearline content into your site is to import the route and create an iFrame in your HTML.

In your HTML include the following:

```
<iframe src="https://www.tearline.mil/embedded/"></iframe>
```

The `iframe` object has several parameters that allow you to change the display of your Tearline widget:

Property	Description
<b>stylesheet</b>	A CSS stylesheet with custom formatting for Tearline content. See <b>Section 2</b> for a detailed explanation.  Ex: <code>https://www.tearline.mil/embedded/?stylesheet="https://www.tearline.mil/embed.css"</code>
<b>tags</b>	An array containing a list of tags for selecting which categories to display. For example:  <code>tags=['arctic','climate']</code>  If you set this parameter, <b>only content from the tagged categories will display</b> .  Ex: <code>https://www.tearline.mil/embedded/?tags=["arctic","climate"]</code>  Available categories: <ul style="list-style-type: none"><li>• arctic</li><li>• china-econ</li><li>• china-military</li><li>• chinese-belt-road-initiative</li><li>• climate</li><li>• navigation</li><li>• human-rights</li><li>• machine-learning</li><li>• north-korea-economy</li><li>• russian-influence</li></ul>

Property	Description
	<ul style="list-style-type: none"> <li>special-economic-zones</li> </ul>

## 2.) Customizing the Embedded Stories

By default, the Tearline site uses Bootstrap 3 styles, however, this can be customized with your own stylesheet. To use your own CSS styles, set the `stylesheet` property on a `PartnerEmbed` object to the absolute URL of a CSS file containing your own style definitions.

The following classes and IDs are applied to HTML elements:

CSS Class/ID	Tag	Description
<code>#public-container</code>	<code>div</code>	The main container holding all of the stories
<code>.public-story-item</code>	<code>div</code>	This class is applied to each div containing a story
<code>.post-cats</code>	<code>div</code>	The list of categories for a story
<code>.public-article-title</code>	<code>div</code>	DIV containing all elements of a the story title
<code>.public-title-header</code>	<code>strong</code>	Formats the title
<code>.public-last-updated</code>	<code>p</code>	Contains the "Last Updated" portion of the story
<code>.public-summary</code>	<code>p</code>	Brief summary description of the story
<code>.read-more</code>	<code>span</code>	Contains the "Read More" link, which opens the story in a new tab

## 3.) Example:

```
<!DOCTYPE html>
<html>
  <head>
    <title>Tearline Articles</title>
  </head>
  <body>
    <iframe
      frameborder="1"
      id="tearline-embed"
      src="https://www.tearline.mil/embedded/?tags=['climate']"
      style="width:1200px; height:500px;">
    </iframe>
  </body>
</html>
```